

## CLAIMS

*What is claimed is:*

- 5           1. A method for requantizing coefficients of a bit stream, the method comprising:  
            receiving a plurality of input coefficients ( $F_i$ ) quantized at an input quantization scale ( $q_i$ ), the input coefficients associated with the bit stream;  
            providing an output quantization scale ( $q_o$ ), wherein the output quantization  
10     scale is greater than the input quantization scale to allow for rate reduction of the bit stream; and  
            transmitting a plurality of output coefficients ( $F_o$ ) quantized at the output quantization scale, wherein the plurality of output coefficients are determined using a formula minimizing the difference between dequantized input coefficients ( $f_i$ ) and  
15     dequantized output coefficients ( $f_o$ ).  
            2. The method of claim 1, wherein the quantized coefficients are DCT coefficients of an MPEG encoded bitstream.  
            3. The method of claim 1, wherein the plurality of input coefficients are associated with an intra macroblock or an inter macroblock.  
20           4. The method of claim 1, wherein the output quantization scale has a larger step size than the input quantization scale.  
            5. The method of claim 1, wherein input and output coefficients are dequantized using the following formula:  
$$f = ((2F + k) \cdot q \cdot w) / 32;$$
  
25     where  $k = 0$  for intra macroblocks,  
             $k = \text{sign}(F)$  for inter macroblocks,  
            “/” denotes integer division with truncation of the result toward zero,  
             $w$  = weighting factor, and  
             $\text{sign}(F) = -1, 0, \text{ or } 1$  if  $F < 0, F = 0, \text{ and } F > 0$  respectively.  
30           6. The method of claim 1, wherein the formula minimizes requantization error.  
            7. The method of claim 6, wherein requantization error is minimized using the following formula:

$$q_{error} = \min |(2F_i + k_i) \cdot q_i \cdot w) / 32 - (2F_o + k_o) \cdot q_o \cdot w) / 32|;$$

where  $k = 0$  for intra macroblocks,

$k = \text{sign}(F)$  for inter macroblocks,

“/” denotes integer division with truncation of the result toward zero,

$w$  = weighting factor, and

5           subfix  $i$  and  $o$  in  $F$ ,  $k$  and  $q$  represent input and output values respectively.

8.       The method of claim 3, wherein output quantized coefficients associated with intra macroblocks are calculated using the following formula:

$$F_o = \text{round}(rF_i);$$

10           where  $r$  is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

9.       The method of claim 8, wherein midpoints are rounded toward 0.

10.      The method of claim 3, wherein output quantized coefficients associated with inter macroblocks are calculated using the following formula:

$$15 \quad F_o = \text{round}\left(\frac{k_i}{2} [2r|F_i| + r - 1]\right);$$

          where  $r$  is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

11.      The method of claim 10, wherein midpoints are rounded toward 0.

12.      An apparatus for requantizing coefficients of a bit stream, the apparatus  
20   comprising:

          an input interface configured to receive a plurality of input coefficients ( $F_i$ ) quantized at an input quantization scale ( $q_i$ ), the input coefficients associated with the bit stream;

          a processor configured to provide an output quantization scale ( $q_o$ ), wherein the  
25   output quantization scale is greater than the input quantization scale to allow for rate reduction of the bit stream; and

          an output interface configured to transmit a plurality of output coefficients ( $F_o$ ) quantized at the output quantization scale, wherein the plurality of output coefficients are determined using a formula minimizing the difference between dequantized input  
30   coefficients ( $f_i$ ) and dequantized output coefficients ( $f_o$ ).

13.      The apparatus of claim 12, wherein the quantized coefficients are DCT coefficients of an MPEG encoded bitstream.

14. The apparatus of claim 12, wherein the plurality of input coefficients are associated with an intra macroblock or an inter macroblock.

15. The apparatus of claim 12, wherein the output quantization scale has a larger step size than the input quantization scale.

5 16. The apparatus of claim 12, wherein input and output coefficients are dequantized using the following formula:

$$f = ((2F + k) \cdot q \cdot w) / 32;$$

where  $k = 0$  for intra macroblocks,

$k = \text{sign}(F)$  for inter macroblocks,

10 “/” denotes integer division with truncation of the result toward zero,

$w$  = weighting factor, and

$\text{sign}(F) = -1, 0, \text{ or } 1$  if  $F < 0, F = 0, \text{ and } F > 0$  respectively.

17. The apparatus of claim 12, wherein the formula minimizes requantization error.

15 18. The apparatus of claim 17, wherein requantization error is minimized using the following formula:

$$q_{\text{error}} = \min |(2F_i + k_i) \cdot q_i \cdot w) / 32 - (2F_o + k_o) \cdot q_o \cdot w) / 32|;$$

where  $k = 0$  for intra macroblocks,

$k = \text{sign}(F)$  for inter macroblocks,

20 “/” denotes integer division with truncation of the result toward zero,

$w$  = weighting factor, and

subfix  $i$  and  $o$  in  $F, k$  and  $q$  represent input and output values respectively.

19. The apparatus of claim 14, wherein output quantized coefficients  
25 associated with intra macroblocks are calculated using the following formula:

$$F_o = \text{round}(rF_i);$$

where  $r$  is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

20. The apparatus of claim 19, wherein midpoints are rounded toward 0.

30 21. The apparatus of claim 14, wherein output quantized coefficients associated with inter macroblocks are calculated using the following formula:

$$F_o = \text{round}\left(\frac{k_i}{2} [2r|F_i| + r - 1]\right);$$

where  $r$  is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

22. The apparatus of claim 21, wherein midpoints are rounded toward 0.

23. A computer readable medium comprising computer code for requantizing  
5 coefficients of a bit stream, the computer readable medium comprising:

computer code for receiving a plurality of input coefficients ( $F_i$ ) quantized at an input quantization scale ( $q_i$ ), the input coefficients associated with the bit stream;

computer code for providing an output quantization scale ( $q_o$ ), wherein the output quantization scale is greater than the input quantization scale to allow for rate  
10 reduction of the bit stream; and

computer code for transmitting a plurality of output coefficients ( $F_o$ ) quantized at the output quantization scale, wherein the plurality of output coefficients are determined using a formula minimizing the difference between dequantized input coefficients ( $f_i$ ) and dequantized output coefficients ( $f_o$ ).

24. The computer readable medium of claim 23, wherein input and output  
15 coefficients are dequantized using the following formula:

$$f = ((2F + k) \cdot q \cdot w) / 32;$$

where  $k = 0$  for intra macroblocks,

$k = \text{sign}(F)$  for inter macroblocks,

20 “/” denotes integer division with truncation of the result toward zero,

$w$  = weighting factor, and

$\text{sign}(F) = -1, 0, \text{ or } 1$  if  $F < 0, F = 0, \text{ and } F > 0$  respectively.

25. The computer readable medium of claim 23, wherein the formula minimizes requantization error.

26. The computer readable medium of claim 25, wherein requantization  
25 error is minimized using the following formula:

$$q_{\text{error}} = \min |(2F_i + k_i) \cdot q_i \cdot w) / 32 - (2F_o + k_o) \cdot q_o \cdot w) / 32|;$$

where  $k = 0$  for intra macroblocks,

$k = \text{sign}(F)$  for inter macroblocks,

30 “/” denotes integer division with truncation of the result toward zero,

$w$  = weighting factor, and

subfix  $i$  and  $o$  in  $F$ ,  $k$  and  $q$  represent input and output values respectively.

27. An apparatus for requantizing coefficients of a bit stream, the apparatus comprising:

means for receiving a plurality of input coefficients ( $F_i$ ) quantized at an input  
5 quantization scale ( $q_i$ ), the input coefficients associated with the bit stream;

means for providing an output quantization scale ( $q_o$ ), wherein the output  
quantization scale is greater than the input quantization scale to allow for rate reduction  
of the bit stream; and

means for transmitting a plurality of output coefficients ( $F_o$ ) quantized at the  
10 output quantization scale, wherein the plurality of output coefficients are determined  
using a formula minimizing the difference between dequantized input coefficients ( $f_i$ )  
and dequantized output coefficients ( $f_o$ ).

28. The apparatus of claim 27, wherein input and output coefficients are  
dequantized using the following formula:

15 
$$f = ((2F + k) \cdot q \cdot w) / 32;$$

where  $k = 0$  for intra macroblocks,

$k = \text{sign}(F)$  for inter macroblocks,

“/” denotes integer division with truncation of the result toward zero,

$w$  = weighting factor, and

20  $\text{sign}(F) = -1, 0, \text{ or } 1$  if  $F < 0, F = 0, \text{ and } F > 0$  respectively.

29. The apparatus of claim 27, wherein the formula minimizes  
requantization error.

30. The apparatus of claim 29, wherein requantization error is minimized  
using the following formula:

25 
$$q_{\text{error}} = \min |(2F_i + k_i) \cdot q_i \cdot w) / 32 - (2F_o + k_o) \cdot q_o \cdot w) / 32|;$$

where  $k = 0$  for intra macroblocks,

$k = \text{sign}(F)$  for inter macroblocks,

“/” denotes integer division with truncation of the result toward zero,

$w$  = weighting factor, and

30 subfix  $i$  and  $o$  in  $F, k$  and  $q$  represent input and output values  
respectively.

31. The apparatus of claim 3, wherein output quantized coefficients  
associated with intra macroblocks are calculated using the following formula:

$$F_o = \text{round}(rF_i);$$

where  $r$  is equal to the input quantization scale divided by the output quantization scale and the round function rounds the result to the nearest integer.

5